

# **ART 732-A MK5**

## **ACTIVE TWO-WAY SPEAKER**

#### **DESCRIPTION**

The ART 732-A is a unique speaker in its category. The titanium dome, 3.0" voice coil neodymium compression driver offers a unique vocal clarity and sound projection. The 12" woofer offers an extremely linear response and a precise, deep low frequency control. The transducers are produced using the most advanced assembly technologies. The amplifier delivers 1400 watts and is controlled by a DSP that takes care of crossover, equalisation, phase control, soft limiting and speaker protections.

#### **FEATURES**

- 131 dB Max SPL
- 1400 WATT 2-way peak power
- 90° x 60°, Wide dispersion constant directivity horn
- Innovative DSP Processing
- 3,0" Titanium diaphragm Compression Driver.
- 12" Woofer
- FiRPHASE Technology
- XBOOST Low Frequencies Enhancer

Rev. J Last update: 17/01/2024



#### **TECHNICAL SPECIFICATIONS**

Max SPL @ Im:	Acoustical specifications	Frequency Response:	50 Hz ÷ 20000 Hz
Horizontal coverage angle: Vertical coverage angle: Vertical coverage angle: Vertical coverage angle:  Compression Driver: Woofer:  Input/Output section Input signat Input connectors: Output connectors: NLR Villand Mic Input Sensitivity: - 22 dBu/+4 dBu Mic Input Sensitivity: - 32 dBu  Processor section  Crossover Frequencies: Controls:  Power section  Total Power: High frequencies: Low frequencies: Low frequencies: Cooling: Connections: VDE  Standard compliance  Safety agency:  Calcor:  Size Height: Width: Depth: Width: Depth: Width: Depth: Weight: Weight:  Shipping information Package Height: Package Width: Package Depth: Package Depth: Package Package Height: Package Depth: Package De			
Transducers  Compression Driver:			
Transducers			
Input/Output section		vertical coverage angle.	
Input/Output section	Transducers	Compression Driver:	1 x 1.0" neo, 3.0" v.c
Input connectors:		Woofer:	12", 2.5" v.c
Output connectors:	Input/Output section	Input signal:	bal/unbal
Input sensitivity:		Input connectors:	XLR, Jack
Processor sectionCrossover Frequencies:700Processor sectionProtections:Thermal, RMSLimiter:Soft LimiterControls:Volume, Boost, MIC/LinePower sectionTotal Power:1400 W PeakHigh frequencies:400 W PeakLow frequencies:000 W PeakCooling:ConvectionConnections:VDEStandard complianceSafety agency:CE compliantPhysical specificationsHardware:2 x MIOHandles:1 on top, 1 each sidePole mount/Cap:YesColor:BlackSizeHeight:637 mm / 25.08 inchesWidth:387 mm / 15.24 inchesDepth:363 mm / 14.29 inchesWeight:17.8 kg / 39.24 lbsShipping informationPackage Height:680 mm / 26.77 inchesPackage Width:440 mm / 17.32 inchesPackage Depth:420 mm / 16.54 inches		Output connectors:	XLR
Processor section  Crossover Frequencies: Protections: Limiter: Controls: Volume, Boost, MIC/Line  Power section  Total Power: High frequencies: Low frequencies: Cooling: Connections: VDE  Standard compliance  Safety agency: CE compliant  Hardware: Handles: Handles: Pole mount/Cap: Color: Black  Size Height: Width: Depth: Depth: Width: Depth: Weight: Weight: Weight:  Shipping information Package Height: Package Width: Package Depth: Package Depth: Pole mount/132 inches Package Width: Package Depth: Package Depth: Package Depth: Pole mount/1624 inches Package Width: Package Depth: Package Depth: Package Depth: Package Depth: Package Depth: Pole mount/16,54 inches Package Width: Package Depth: Package Vidth: Package Depth: Package Vidth: Package Vi		Input sensitivity:	-2 dBu/+4 dBu
Protections:		Mic. Input Sensitivity:	-32 dBu
Limiter:   Controls:   Volume, Boost, MIC/Line	Processor section	Crossover Frequencies:	700
Power section		Protections:	Thermal, RMS
Power section		Limiter:	Soft Limiter
High frequencies:		Controls:	Volume, Boost, MIC/Line
Low frequencies:	Power section	Total Power:	1400 W Peak
Cooling:         Convection           Connections:         VDE           Standard compliance         Safety agency:         CE compliant           Physical specifications         Hardware:         2 x M10           Handles:         1 on top, 1 each side           Pole mount/Cap:         Yes           Color:         Black           Size         Height:         637 mm / 25.08 inches           Width:         387 mm / 15.24 inches           Depth:         363 mm / 14.29 inches           Weight:         17.8 kg / 39.24 lbs           Shipping information         Package Height:         680 mm / 26.77 inches           Package Width:         440 mm / 17.32 inches           Package Depth:         420 mm / 16.54 inches		High frequencies:	400 W Peak
Connections:   VDE		Low frequencies:	1000 W Peak
Standard compliance         Safety agency:         CE compliant           Physical specifications         Hardware:         2 x M10           Handles:         1 on top, 1 each side           Pole mount/Cap:         Yes           Color:         Black           Size         Height:         637 mm / 25.08 inches           Width:         387 mm / 15.24 inches           Depth:         363 mm / 14.29 inches           Weight:         17.8 kg / 39.24 lbs           Shipping information         Package Height:         680 mm / 26.77 inches           Package Width:         440 mm / 17.32 inches           Package Depth:         420 mm / 16.54 inches		Cooling:	Convection
Physical specifications         Hardware:		Connections:	VDE
Handles:   1 on top, 1 each side   Pole mount/Cap:   Yes	Standard compliance	Safety agency:	CE compliant
Pole mount/Cap: Yes	Physical specifications	Hardware:	2 x M10
Size       Height:       637 mm / 25.08 inches         Width:       387 mm / 15.24 inches         Depth:       363 mm / 14.29 inches         Weight:       17.8 kg / 39.24 lbs         Shipping information       Package Height:       680 mm / 26.77 inches         Package Width:       440 mm / 17.32 inches         Package Depth:       420 mm / 16.54 inches		Handles:	1 on top, 1 each side
Size       Height:       637 mm / 25.08 inches         Width:       387 mm / 15.24 inches         Depth:       363 mm / 14.29 inches         Weight:       17.8 kg / 39.24 lbs         Shipping information       Package Height:       680 mm / 26.77 inches         Package Width:       440 mm / 17.32 inches         Package Depth:       420 mm / 16.54 inches		Pole mount/Cap:	Yes
Width:   387 mm / 15.24 inches		Color:	Black
Depth:       363 mm / 14.29 inches         Weight:       17.8 kg / 39.24 lbs         Shipping information       Package Height:       680 mm / 26.77 inches         Package Width:       440 mm / 17.32 inches         Package Depth:       420 mm / 16.54 inches	Size	Height:	637 mm / 25.08 inches
Weight: 17.8 kg / 39.24 lbs  Shipping information Package Height: 680 mm / 26.77 inches Package Width: 440 mm / 17.32 inches Package Depth: 420 mm / 16.54 inches		Width:	387 mm / 15.24 inches
Shipping information Package Height: Package Width: Package Depth:  420 mm / 16.54 inches		Depth:	363 mm / 14.29 inches
Package Width: 440 mm / 17.32 inches Package Depth: 420 mm / 16.54 inches		Weight:	17.8 kg / 39.24 lbs
Package Depth: 420 mm / 16.54 inches	Shipping information	Package Height:	680 mm / 26.77 inches
		Package Width:	440 mm / 17.32 inches
Package Weight: 20.6 kg / 45.42 lbs		Package Depth:	420 mm / 16.54 inches
		Package Weight:	20.6 kg / 45.42 lbs



### **PART NUMBER**

· 13000856

ART 732-A MK5 100-120V

EAN 8024530021542

· 13000825

ART 732-A MK5 220-240V

EAN 8024530021474



ACCESSORIES			
	AC PMX POLE MOUNT M20	PART NUMBER EAN:	<b>13360232</b> 8024530010058
	AC PRO-FS PROFESS. LOCKING FLOOR STAND	PART NUMBER EAN:	<b>13360109</b> 8024530006471
a a	AC PRO-PM PROFESS. LOCKING POLE MOUNT	PART NUMBER EAN:	<b>13360110</b> 8024530006488
₩	COVER CVR ART 722	PART NUMBER EAN:	<b>13360114</b> 8024530010669
	HORIZONTAL BRACKET H-BR 2X ART 712	PART NUMBER EAN:	<b>13360104</b> 8024530015855
7	POLE MOUNT KIT PM-KIT M20	PART NUMBER EAN:	<b>13360067</b> 8024530014599