

S 19

HIGH-POWER BASS REFLEX SUBWOOFER

DESCRIPTION

S 19 is a high-power single 19" subwoofer suitable for RCF Installed Sound systems. The bass-reflex design ensures an efficient acoustic response down to 30 Hz. The high-quality plywood cabinet is finished with a black, heavy-duty polyurea coating and protected by a powder-coated metal grille. The recessed input panel features two Speakon NL4 connectors, allowing a quick and safe connection. A M20 pole mount adaptor on top of the cabinet and handles on both sides are provided. Both models can be ground-stacked and are cardioid-arrayable for improved rear rejection.



FEATURES

- Up to 1500 W power handling
- 139 dB max SPL
- 30 ÷ 200 Hz frequency range
- 19" HyperVented Neodymium Woofer with 4" v.c.
- High-quality polyurea-coated multi-ply cabinet
- Steel front grille with clothing
- M20 standard pole mount in top end of cabinet
- Speakon NL4 connectors

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response (-10dB)	30 Hz ÷ 200 Hz
	Max SPL @ 1m	139 dB
Power section	Amplification	Full Range
	Nominal Impedance	8 ohm
	Power Handling	1500 W
	Peak Power Handling	6000 W PEAK
Transducers	Woofers	19" neo, 4.0" v.c
Input/Output section	Input connectors	Speakon® NL4
	Output connectors	Speakon® NL4
Standard compliance	Safety agency	CE compliant
Physical specifications	Handles	2 side
	Pole mount/Cap	Yes
Size	Height	534 mm / 21.02 inches
	Width	650 mm / 25.59 inches
	Depth	730 mm / 28.74 inches
	Weight	44 kg / 97 lbs
Shipping information	Package Height	565 mm / 22.24 inches
	Package Width	680 mm / 26.77 inches
	Package Depth	760 mm / 29.92 inches
	Package Weight	48 kg / 105.82 lbs

PART NUMBER

- **13100096**

S 19

EAN 8024530021740

