

Key features:

- Reflex-loaded double 8" low frequency enclosure
- Compact fibreglass enclosure
- Marine-grade stainless steel fittings
- UV-resilient paint
- Weather-protected with an IP-55 rating (BS EN 60529:1992 +A2:2013)
- Polished stainless steel bracket included



Cyclone 208 is a compact subwoofer designed for pairing with Cyclone 4 or Cyclone 55 in order to create a high-output and stylish sound system. An IP-55 rating and an integrated polished stainless-steel bracket, allow for all-weather applications in a wide range of environments.

Despite its discreet dimensions, Cyclone 208 features dual 8" low frequency transducers, which combined with its low resonance fibreglass enclosure results in exceptional output and extension capabilities. Its compact nature allows installation in listening environments where floor space is premium and for those desiring the highest levels of fidelity. Perfectly positioned to meet the installation demands of smaller bars and restaurants, beach clubs, retail establishments, theme parks and marine based applications.

Specifications

Frequency response	42 Hz - 120 Hz ± 3 dB
Efficiency ¹	95 dB 1 W / 1 m
Nominal impedance	8 Ω
Power handling ²	300 W
Maximum output ³	119 dB Cont, 125 dB Peak
Driver configuration	2 x 8" LF
Connectors	Phoenix connector with link out
Weight	22 kg (48.5 lbs)
Enclosure	Fibreglass composite
Mounting	Ground stack bracket
Finish	Smooth cellulose

¹ Measured in half space ² AES2 - 1984 compliant ³ Calculated

